



*A "Green" alternative  
for delicious water  
throughout the  
whole house!*

**M**any people today are looking for alternatives to standard water treatment methods. Hague Quality Water is committed to providing customers who have these environmental concerns with an effective product to improve their water.

Hague's NEW **ULTRAMAX** is a salt free filtration system that uses Activated Carbon and KDF 55. This innovative combination makes an excellent whole-house filter that removes tastes and odors, offers excellent chlorine and organic reduction, filters the water down to 20 microns, plus does not require a regenerate. Like other Hague products, this new whole-house filter features water and energy saving technology; great benefits for customers and the environment.

Hague's 62ABE-BWO  
ULTRAMAX Filter



### *The ULTRAMAX Advantage:*

- Salt Free Filtration System
- 10 Year Warranty To Take Out Chlorine
- Filters Sediment To Improve Water Conditions down to 20 microns
- Ideal filtration unit where softening is not required

 **HAGUE**  
Quality Water®

*Contact your local Hague Dealer today to learn more about "Salt Free" filtration alternatives!*

# The ULTRAMAX Filter

## The "Green" Alternative For Brine Restricted Areas.

### Hague's 62ABE-BWO ULTRAMAX Filter Specifications

Capacity-ppm	N/A
Sulfur H2O	N/A
Iron-ppm	N/A
Chlorine-ppm	3
Minimum pH	N/A
Media type and amount - cu. ft. (L)	Chlorostat - 14 lbs ( 6.3 kg)
	Ultra-fil - 6 lbs (2.7 kg)
	Activated Carbon -21lbs (9.5 kg)
Cont. flow rate-gpm (L/min)	6 (23)
Peak flow rate-gpm (L/min)	10 (38)
Backwash rate-gpm (L/min)	7 (26)
Brine line flow control-gpm (L/min)	N/A
Water Pressure-psi. (bar)	30-120 (2.1 - 8.3)
Mode settings	1
Backwash #1-min	7
Brine/Rinse -min	0
Backwash #2-min	0
Salt (lbs)	N/A
Regenerant used	N/A
Flow rate at 25 psi (1.7 bar) drop-gpm (L/min)	18 (68)
Flow rate at 15 psi (1.0 bar) drop-gpm (L/min)	13.8 (52)
Service flow in gpm (L/min) @ pressure drop in psi bar	8 @ 5.2 (30.2 @ .3 bar)

For optimum water quality, do not exceed recommended service flow rate. Backwash unit every 3 days or as needed.

